Cyntec

Current Sensing Resistor

VSRP0612W2 Series Current Sensing Resistor (Lead / Halogen Free)

Features / Applications :

- High power rating is up to 2W
- Low TCR (±200 ppm/°C)
- Current sensing resistor for power supplies, motor circuits, etc.
- RoHS compliant & AEC-Q200 qualified
- Suitable for reflow soldering
- Excellent heat dissipation by wide terminal type



Electrical Specifications :

Characteristics	Feature			
Power Rating*	2 W			
Resistance Range	$0.01\Omega{\sim}0.15\Omega$	0.091 $\Omega{\sim}$ 0.15 Ω		
Temperature Coefficient of Resistance(ppm/°C)	±200	±100		
Resistance Tolerance	±1%(F), ±2%(G), ±5%(J)	0.5%(D)		
Operation Temperature Range	-55°C ~	+155℃		

*Note :

For sensor operated at ambient temperature in excess of 70°C, the maximum load shall be derated in accordance with the following curve.



DOCUMENT : CYNP-74-A01



Current Sensing Resistor

Outline Drawing :



Type Designation :

VSRP	0612	W	2 -		
(1)	(2)	(3)	(4) -	(5)	(6)

Note :

- (1) Series No.
- (2) Size
- (3) Terminal type : W = Wide terminal
- (4) Power Rating : 2 = 2W
- (5) Resistance value:

The "R" shall be used as a decimal point, For example --

 $R010 = 0.01\Omega;$

(6) Tolerance (%)

F=±1%, G=±2%, J=±5%

DOCUMENT : CYNP-74-A01



Current Sensing Resistor

Recommend Land Pattern Dimensions :



Size	W	L	D	t
	(mm)	(mm)	(mm)	(mm)
1632W	3.30	2.80	1.10	0.140

t: Copper foil minimum thickness of PCB

Packaging :

Tape packaging dimensions







Current Sensing Resistor

Reel dimensions



Numbers of Taping : 4,000 pieces /reel

The following items shall be marked on the reel.

- (1) Type designation.
- (2) Quantity
- (3) Manufacturing date code
- (4) Manufacturer's name

Peel force of top cover tape

The peel speed shall be about 300 mm/min. The peel force of top cover tape shall be between 0.1 to 0.7 N.



DOCUMENT : CYNP-74-A01



Care Note :

Care note for storage

- (1) Chip resistor shall be stored in a room where temperature and humidity must be controlled. (temperature 5 to 35° C, humidity 45 to 85% RH) However, a humidity keep it low, as it is possible.
- (2) Chip resistor shall be stored as direct sunshine doesn't hit on it.
- (3) Chip resistor shall be stored with no moisture, dust, a material that will make solderability inferior, and a harmful gas (Chloridation hydrogen, sulfurous acid gas, and sulfuration hydrogen).

Care note for operating and handling

- (1) It is necessary to protect the edge and protection coat of resistors from mechanical stress.
- (2) Handle with care when printing circuit board (PCB) is divided or fixed on support body, because bending of printing circuit board (PCB) mounting will make mechanical stress for resistors.
- (3) Resistors shall be used with in rated range shown in specification. Especially, if voltage more than specified value will be loaded to resistor, there is a case it will make damage for machine because of temperature rise depending on generating of heat, and increase resistance value or breaks.
- (4) In case that resistor is loaded a rated voltage, it is necessary to confirms temperature of a resistor and to reduce a load power according to load reduction curve, because a temperature rise of a resistor depends on influence of heat from mounting density and neighboring element.
- (5) Observe Limiting element voltage and maximum overload voltage specified in each specification
- (6) If there is possibility that a large voltage (pulse voltage, shock voltage) charge to resistor, it is necessary that operating condition shall be set up before use.